

NIGHTLINE, INC.

NIGHT VISION SPECIALISTS



IntelliVuPLUS™ Automatic Day-Night Sensor



New! IntelliVuPLUS™

System configuration enhances surveillance CCTV and zoom lenses providing Day / Night vision capability.



SYSTEM SPECIFICATIONS	
- Magnification	Depends on Obj. Lens
- Focus Range	1m to infinity
- Lens Requirements (C-Mount recommended)	1" or 1/2" C/CS-Mount
- CCD Camera Requirements	1/2" or 1/3" CS-Mount
- Light Level (from sunny day to nighttime)	10,000 lx to 0.0001 lx
- Sensitivity (with f/1.4 lens)	0.00001 fc (overcast)
• IMAGE INTENSIFIER	
- Resolution (Gamma or Delta Version)	57 lp/mm or 64 lp/mm
• ELECTRICAL	
- Power Supply (please indicate)	12 VDC or 24 VAC
• VIDEO	
- Signal Protocol	NTSC / PAL / SECAM
- Automatic Gain Control	Lens connected to CCD
- Iris	Auto-Iris
• IP-based Web Camera (OPTIONAL)	
- Video Standard Real Time Compression	MPEG-4 @ 30 fps
- Configuration	Via Web Browser
- PTZ support	most cameras
• ENVIRONMENTAL	
- Operating Temperature	+0° to +122°F
- Storage Temperature	-31° to +158°F
- Humidity	Up to 95%
• MECHANICAL	
- Weight (IntelliVu PLUS)	3-1/2 lbs
- Dimensions (IntelliVu PLUS)	5.1 L x 4.5 W x 4" H